

KP-150 PRODUCTION HOSE CRIMPER MAX. 1 1/4" (DN32,-20)



OPTIONAL

- Pressure monitoring
- Oil cooling
- Data record & transfer

Fast cycle, slim frame, large opening & silent hydraulics

Indicative Hose Capacity :

2-SN & industrial BP.....2" (DN50)

4-SP/R12.....1 1/4" (DN32)

R13/R15/4-SH or Interlock1" (DN25)

Max hose diameter.....Ø76mm 1" (with die N°70)

Motor / Electrics : 5.5 kW - 230/400V 3-PH 50Hz

Radial press force : 140 tons

Opening : Ø Die size+ 45mm

Opening without dies : 125 mm

Master die shoe length : 80mm

Available die sizes (mm) :

Ø 6/8/10/12/15/18/21/24/27/30/33/36/39/42/45/48/51/54/57/66/70 MM

Controls :

Touch screen HMI

Intuitive crimp software with Semi auto mode, memory of crimp parameters , automatic die selection, quick change, cycle counter.

Speed :

Closing speed : 22mm/s

Crimp speed : 3.7mm/s

Opening speed : 66mm/s

Number of cycles/hour : 2000 (in semi -auto mode, die Ø+10mm)

Dimensions :

Width : 630mm / Depth : 450mm / Height: 590mm

Net weight (with full oil tank) : 720 Kg (180l)

Packing :

Crate size : 90x85x141cms / Gross weight : 830kgs

Noise level : < 64 dB(A)

Die Chart

Ø	6	8	10	12	15	18	21	24	27	30
L(mm)	56	56	56	70	70	70	70	70	70	70

Ø	33	36	39	42	45	48	51	54	57	66	70
L(mm)	70	70	70	70	70	70	70	70	70	70	70

