


NK-60 ELECTRIC HOSE CRIMPING MACHINE MAX. 4" (DN100, -64)



OPTIONAL



Powerful workshop crimping machine with large opening.
Head protected with foam inserts

Indicative Hose Capacity :

2-SN and Industrial Low Pressure..... 4" (DN100; -64)
4-SP/R122" (DN50; -32)
4SH/R13/R15/Interlock : 2" (DN50; -32) acc. to fitting material
Max. size for assembly with 2 x 90° elbows : max. 3" (DN63)

Motor / Electrics :

4 kW - 230/400V 3-PH
4 kW - 230V 1-PH (25A)

Radial press force : 350 tons

Opening : Die size + 54 mm (Press path +15 mm)

Opening without dies : 182mm

Master die shoe length : 120mm

Available die sizes (mm) :

Ø 6/10/12/15/18/21/24/27/30/33/36/39/45/48/51/57/66/73/80/86
/90//95/99/112/117/122/130/136 MM

Dimensions :

Width 800mm/ Depth : 440mm
Height : 800mm

Net weight (with full oil tank, w/o dies) : 235 Kg

Packing :

Wooden crate conform to ISPM15
Crate size : 110x78x110cms
Gross weight (with 5 sets of dies) : 300 kgs

Noise Level:

< 70 dB(A) with standard hydraulic pump
< 63 db(A) with optional silent pump (ELIKA)

Die Chart

Ø	6	8	10	12	15	18	21	24	27	30	33	36	39	42	45	48
L (mm)	56	56	56	56	56	56	56	70	70	70	70	70	70	70	100	100
Ø	51	54	57	66	70	73	80	86	90	95	99	112	117	122	130	136
L (mm)	100	100	100	100	100	120	120	120	120	120	120	120	120	120	120	120

