


NK-30-DC/12V


Crimping Machine for mobile van for hoses up to 1.1/4" (DN32, -20)



60 kg



Easy to use, compact & balanced unit,
ULTRA LIGHT



35 kg

Available with head separated from power pack
(Ref. NKS-30)



- Capacity up to 4-SP - 1.1/4"
- Interlock, R13, 6-Wire assemblies up to 1"
- Compact and Light Unit thanks to aluminium head
- Head protected with foam pads between dies
- Easy maintenance and servicing

- ACCESSORIES & OPTIONS**
- Quick Change Tool (QCT-NLS)
 - Die Storage Panel (WP-12PDR)
 - Individual Die Storage Pods (PDR-1)

Technical Specifications NK-30-DC / 12V	
Max. capacity: <i>For intermittent use in assembling high pressure hoses</i>	2-SN & Industrial 2" (DN50; -32) 4-SP/R12 1.1/4" (DN32; -20) R13/R15/4-SH/Interlock 1" (DN25, -16) Limit with 2 x 90 deg. elbows 90 max.. 1" (DN25) Max Crimp range..... 70mm (with Dies N°66)
Motor / Electricity	2 000 W - 12 V.DC <i>Must be connected to 12 VDC Battery 250 Amp/ hour. Battery is not supplied with the machine</i>
Radial Crimp Force	130 Tons
Opening with dies	∅ Die + 28mm
Press path	∅ Die + 12mm
Opening with dies	98mm
Length master dies	75mm
Machine dimensions (mm)	630x450x590mm
Net weight (with oil HV32, without dies)	NK30-DC-12V : 60 Kg Weight Head Only with Support Bracket (NKS-30): 35 Kg
Standard packing (for transport)	Wooden crate conform to NIMP15 norms Crate dimensions : 58x70x75cm Gross weight (with 5 sets of dies) : 95 Kg
Noise level	< 70 dB(A)

∅ Die	Length (mm)
6	56
10	56
12	56
15	56
18	56
21	56
24	70
27	70
30	70
33	70
39	70
45	70
48	70
51	70
57	75
66	75

ALSO AVAILABLE 12V HOSE CUTTER



NC-30-DC